

A Tale of Two Roads: Consequences of Peat Conditions and Construction Practices on Peatland Effects, Reclaimability, and Best Practice Development

Terry Osko
Circle T Consulting, Inc.

DUC Wetland BMP Workshop, 21 January 2016

Outline

- Describe two experimental road reclamation projects:
 - Site characteristics
 - Study objectives
 - Work completed
 - Observations and insights
- Compare/Contrast Site-specific Consequences
 - Site impacts
 - Reclaimability
 - Post-reclamation recovery
- Implications for Best Practice Selection/Development



Project 1: JACOS

- Deep peat ☹️
- Deep fill ☹️
- Clayey Surficial Deposit ☹️
- Low volume, slow flow of water 😊




JACOS HANGINGSTONE PROJECT

Site Description





Site Detail: Road Cross-Section



Fill Removal Choices

- Remove all fill from the road
 - Difficult and expensive
 - Leaves open pool of water
 - Should restore hydrologic continuity

- Lower fill to within water table
 - Leaves surface for revegetation
 - Difficulty?
 - Hydrologic continuity?




Project Objectives


- Characterize ecohydrologic conditions
 - Water table
 - Soil moisture
 - Vegetation
 - Carbon and nutrient dynamics
- Determine whether partial fill removal restores natural drainage and measure impacts on ecohydrology
- Evaluate revegetation methods for road surface

Project Plan

- Document pre-excavation conditions
 - Water wells
 - Carbon exchange
 - Peat properties
 - Nutrient cycling
- Estimate excavation depth based on water table depths
- Excavate
- Apply revegetation treatments
- Measure responses




Road Excavation




- 2 prior seasons of water table observations
- 3 excavations as replicate “blocks”
- January excavation
 - Reduced impact from equipment
 - Logistically easier
 - Still some water flow




Mean Water Elevation by Year



Water Table Level



Soil Moisture




Impact Summary

- Road has impeded water flow
 - Water table and moisture differences between upstream and downstream sides of road
 - Some impact on vegetation
 - Minor impact on peat
 - Little impact on carbon and nutrient dynamics
 - Impacts may have been greater with higher water flow
- Lowering road surface did not sufficiently improve water flow
- Water table differential on opposite sides of road make managing water table on road difficult


Relative Water Table Position

- Water table is below soil surface both upstream and downstream
- Water table is above soil surface on road for at least part of the year
 - Excavation surface is lower than adjacent peat surface
- Fill surface is poor substrate and difficult to revegetate

Water Table Level



Road Cross-Section After Excavation




Long periods of
flooding hinder
revegetation efforts



Recommendations

- Crown road to improve surface drainage
 - Cut drainage channels also?
- Fill excavation with stockpiled peat
- Improve porosity of road (culverts, deep channels, remove sections of road)



Project 2: Suncor

- Shallower peat 😊
- Shallower fill 😊
- Sandy Surficial Deposit 😊
- Low volume, slow flow of water 😊



Site Description



- Gravel-capped clay fill road on fabric liner over fen peatland.
 - 250 m long
 - 6 years old
- Clay thickness: 1.4 – 1.7 m
- Compressed peat thickness: 0.7 – 1.4 m
- Underlain by sand
- Evidence of vegetation mortality due to flooding on the upstream side

Objectives

- Remove fill entirely
- Re-use the fill
- Achieve natural revegetation of re-exposed peat to an acceptable peatland community
- New peatland community naturally sustainable by restoration of suitable hydrologic regime

Questions/Unknowns

- Will the road fill be reusable? If so, how much of it?
- Will the buried, compressed peat decompress naturally?
- Will the peat regain its pre-disturbance hydrologic properties?
- Will favourable hydrologic conditions establish on their own?
- Plus other questions – e.g. revegetation

Road Removal Process

- Progressively removed fill and carefully removed liner from one end to the other
- Pumped water off at excavation front to keep working area “dry”
- Organics and very wet soil along apron, as well as liner and geo-grid separated and land-filled
- Drier material hauled nearby onsite for parking lot construction
- Start to finish approximately two weeks, 10 full days of work














Soil Moisture and Density Analysis

- Estimated maximum density:
- 1844 (kg/m³)
- Estimated optimum moisture to achieve max density: 13.8%
- Moisture of samples:
- Mean = 11.5%
- Range = 8.1% - 14.2%
- (2 of 72 samples >13.8%)



(From: AB Transportation Method TLT-413 (02))

Moisture Trends in Road Profile (% moisture)

	Upstream Shoulder	Middle	Downstream Shoulder	Depth Average
0-25 cm	9.4 ^{a1}	9.0 ^{a1}	10.3 ^{a1}	9.5^a
25-50 cm	10.9 ^{b1}	10.5 ^{b1}	12.7 ^{bc2}	11.4^b
50-75 cm	10.0 ^{a1}	11.8 ^{c2}	11.7 ^{b2}	11.2^b
75-100 cm	11.9 ^{bc1}	11.8 ^{bc1}	12.9 ^{bc1}	12.2^c
100-125 cm	12.4 ^{c1}	11.5 ^{bc1}	12.7 ^{bc1}	12.2^c
125-150 cm	12.3 ^{c1}	12.2 ^{c1}	13.4 ^{c1}	12.6^c
Position Average	11.1¹	11.1¹	12.2²	

Fill Volumes



- Total volume of fill removed (m^3):
 - Gravel: 181
 - Mud, organics, liner material: 987
 - Useable clay: 4866
- Useable clay as a proportion of clay fill = 83.1%

Road Fill Summary

- Bulk of fill (83%) immediately reusable
- Soil quality excellent
- Much cheaper than a new borrow if the fill can be used nearby
- Less footprint than new borrow also, thereby reducing reclamation liability
- Excavation was not complicated, probably depends on depth of fill, depth and nature of underlying peat, initial construction



Peat Response Summary

- While compressed, formerly buried peat surface showed seasonal oscillations with moisture conditions, therefore decompressing naturally.
- Physical and hydrologic properties of previously buried peat within natural ranges
 - Additional evidence that properties able to restore naturally.
 - Increasingly likely if appropriate vegetation establishes
- Additional interventions likely not required.

Review of Impacts


- JACOS

- Road disrupted hydrology, with impacts on vegetation
- Logistically difficult to remove road impacts
- Impacts not addressed by just lowering road surface
- Vegetation effects permanent



Review of Impacts

- Suncor
 - Road had minimal impact on hydrology
 - Removal of road was easy
 - Hydrology and peat properties will likely recover naturally
 - Likely to achieve acceptable revegetation naturally




Implications for Best Practices

- Reclamation of Existing Roads
 - No reason not to try to fully remove relatively shallow fill from relatively shallow peat
 - While difficult to remove fill from below water line, fill quality is likely acceptable (i.e. road failure if fill was saturated)
- Managing Future Footprint (Wetland Policy)
 - Avoidance
 - Minimization
 - Compensation (reclamation)

Better Planning = Better Practices

- Avoidance, Minimization, Compensation (Reclamation)
 - Avoid undesirable impacts, not necessarily peatlands
 - Evaluate peatland conditions
 - Select route options
 - Adopt condition-specific practices
 - Adopt practices already proven elsewhere (e.g. Scotland – proper pre-loading of peat)
 - Plan to make reclamation easy
 - Following the strategies of avoiding negative impacts and adopting condition-specific practices will reduce reclamation difficulty and improve reclamation success



Thanks!

- CAPP - PTAC
- Alberta-Pacific Forest Industries
- Canadian Natural
- Cenovus
- ConocoPhillips Canada
- Devon Canada
- Husky Energy
- Imperial Oil
- Japan Canada Oil Sands
- MEG Energy
- Nexen Energy ULC
- Statoil Canada
- Suncor Energy
- University of Alberta
- University of Waterloo